Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 2

Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the

subject application:

1. (currently amended) A communication terminal device provided with a function of

rejecting receipt of messages from communication partners other than communication partners

previously registered in receipt-allowed communication partner registration table, said

communication terminal device comprising:

a receipt rejecting communication control medium collecting communication control

information in connection with a communication relating to a message arrival from a

communication partner not registered in said receipt-allowed communication partner registration

table and storing said collected communication control information in a signal-receiving rejecting

communication control information storage medium;

a communication control list creating medium creating a list of image information on the

basis of said communication control information stored in said signal-receiving rejecting

communication control information storage medium; and

a list outputting medium visibly outputting said list of image information created by said

communication control list creating medium,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registration

table is rejected, a message receiving process is not performed by said communication terminal

device for the receipt-rejected communication, and

wherein for a receipt-rejected communication partner, said list of image information

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 3

~~includes communication control information for~~ shows a plurality of rejected communications, ~~and the communication control information in the list for a rejected communication indicates that the communication was rejected~~ from the receipt-rejected communication partner including for each rejected communication from the receipt-rejected communication partner the date and time of the rejected communication.

2. (currently amended) A method of controlling a communication terminal device provided with a function of rejecting receipt of messages from communication partners other than communication partners previously registered in a receipt-allowed communication partner registration table, said method comprising:

collecting communication control information in connection with a communication relating to a message arrival, from a communication partner not registered in said receipt-allowed communication partner registration table and storing said collected communication control information in a signal-receiving rejecting communication control information storage medium;

creating a list of image information on the basis of said communication control information stored in said signal-receiving rejecting communication control information storage medium; and

visibly outputting said created list of image information,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registration table is rejected, a message receiving process is not performed by said communication terminal device for the receipt-rejected communication, and

wherein for a receipt-rejected communication partner, said list of image information

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 4

~~includes communication control information for~~ shows a plurality of rejected communications; ~~and the communication control information in the list for a rejected communication indicates that the communication was rejected~~ from the receipt-rejected communication partner including for each rejected communication from the receipt-rejected communication partner the date and time of the rejected communication.

3. (currently amended) A communication terminal device provided with a function of rejecting receipt of messages from communication partners other than communication partner previously registered in a receipt-allowed communication partner registration table, said communication terminal device comprising:

a normal communication control medium collecting communication control information in connection with a communication relating to receipt of a message from a communication partner registered in a transmission-allowed communication partner registration table or said receipt-allowed communication partner registration table, and storing said collected communication control information in a normal communication control information storage medium;

a receipt-rejected communication control medium collecting communication control information in connection with a communication relating to a message arrival from a communication partner not registered in said receipt-allowed communication partner registration table and storing said collected communication control information in a receipt-rejected communication control information storage medium;

a communication control list creating medium creating a communication control list such that lists image information based on the communication control information respectively stored

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 5

in said normal communication control information storage medium and said receipt-rejected

communication control information storage medium, wherein the communication control

information in connection with the communication relating to the message arrival from the

communication partner not registered in said receipt-allowed communication partner registering

table can be discriminated from the communication control information in connection with the

communication relating to the receipt of the messages from the communication partner registered

in a transmission-allowed communication registering table; and

a list outputting medium visibly outputting the list of image information created by said

communication control list creating medium,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registration

table is rejected, a message receiving process is not performed by said communication terminal

device for the receipt-rejected communication, and

wherein <u>for a receipt-rejected communication partner</u>, said list of image information

~~includes communication control information for~~ <u>shows</u> a plurality of rejected communications,

~~and the communication control information in the list for a rejected communication indicates that~~

~~the communication was rejected~~ <u>from the receipt-rejected communication partner including for</u>

<u>each rejected communication from the receipt-rejected communication partner the date and time</u>

<u>of the rejected communication.</u>

4. (currently amended) A method of controlling a communication terminal device

provided with a function of rejecting receipt of messages from communication partners other

than communication partners previously registered in a receipt-allowed communication partner

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 6

registration table, said method comprising:

collecting communication control information in connection with communication relating

to receipt of a message from [[the]] a communication partner registered in a transmission-allowed

communication partner registration table or said receipt-allowed communication partner

registration table, and storing said collected communication control information in a normal

communication control information storage medium;

collecting [[said]]] communication control information in connection with [[the]] a

communication relating to [[the]] message arrival from [[the]] a communication partner not

registered in said receipt-allowed communication partner registration table;

storing said corrected communication control information in a receipt-rejected

communication control information storage medium;

creating a communication control list that lists image information based on the

communication control information respectively stored in said normal communication control

information storage medium and said receipt-rejected communication control information storage

medium, wherein the communication control information in connection with the communication

relating to the message arrival from the communication partner not registered in said receipt-

allowed communication partner registering table can be discriminated from the communication

control information in connection with the communication relating to the receipt of the messages

from the communication partner registered in the transmission-allowed communication

registering table; and

visibly outputting the communication control list of image information,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registration

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 7

table is rejected, a message receiving process is not performed by said communication terminal

device for the receipt-rejected communication, and

wherein <u>for a receipt-rejected communication partner,</u> said list of image information

~~includes communication control information for~~ <u>shows</u> a plurality of rejected communications,

~~and the communication control information in the list for a rejected communication indicates that~~

~~the communication was rejected~~ <u>from the receipt-rejected communication partner including for</u>

<u>each rejected communication from the receipt-rejected communication partner the date and time</u>

<u>of the rejected communication.</u>

5. (original) The communication terminal device as defined in claim 1, wherein said

communication control information collected by said receipt rejecting communication control

medium and stored in said receipt-rejected communication control information storage medium

in connection with the communication relating to the message arrival from the communication

partner not registered in said receipt-allowed communication partner registering table includes

communication partner discriminating information notified at the time of the message arrival.

6. (original) The communication terminal device as defined in claim 3, wherein said

communication control information collected by said receipt rejecting communication control

medium and stored in said receipt-rejected communication control information memorizing

medium in connection with the communication relating to the message arrival from the

communication partner not registered in said receipt-allowed communication partner registering

table includes communication partner discriminating information notified at the time of the

message arrival.

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 8

7. (original) The method of controlling the communication terminal device as defined in claim 2, wherein said communication control information stored in said signal-receiving rejecting communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the communication partner discriminating information notified at the time of the message arrival.

8. (original) The method of controlling the communication terminal device as defined in claim 4, wherein said communication control information stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes communication partner discriminating information notified at the time of the message arrival.

9. (original) The communication terminal device as defined in claim 1, further comprising:

a time counting medium for counting a present date and time,

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting

medium at the time of the message arrival.

10. (original) The communication terminal device as defined in claim 3, further comprising:

a time counting medium for counting a present date and time,

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

11. (original) The communication terminal device as defined in claim 5, further comprising:

a time counting medium for counting a present date and time

wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storage medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes the date-and-time information read out from said time counting medium at the time of the message arrival.

12. (original) The communication terminal device as defined in claim 6, further

Koichiro MAEMURA, S.N. 09/653,994
Page 10

comprising:

a time counting medium for counting the present date and time

wherein the communication control information collected by said receipt-rejected

communication control medium and stored in said receipt-rejected communication control

information storage medium in connection with the communication relating to the message

arrival from the communication partner not registered in said receipt-allowed communication

partner registering table includes the date-and-time information read out from said time counting

medium at the time of the message arrival.

13. (original) The communication terminal device as defined in claim 2, wherein the

communication control information stored in said receipt-rejected communication control

information storage medium in connection with the communication relating to the message

arrival from the communication partner not registered in said receipt-allowed communication

partner registering table includes date-and-time information at the time of the message arrival.

14. (original) The communication terminal device as defined in claim 4, wherein the

communication control information collected by said receipt-rejected communication control

medium and stored in said receipt-rejected communication control information storage medium

in connection with the communication relating to the message arrival from the communication

partner not registered in said receipt-allowed communication partner registering table includes

date-and-time information at the time of the message arrival.

15. (original) The communication terminal device as defined in claim 7, wherein the

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 11

communication control information collected by said receipt-rejected communication control

medium and stored in said receipt-rejected communication control information storage medium

in connection with the communication relating to the message arrival from the communication

partner not registered in said receipt-allowed communication partner registering table includes

date-and-time information at the time of the message arrival.

16. (original) The communication terminal device as defined in claim 8, wherein the

communication control information collected by said receipt-rejected communication control

medium and stored in said receipt-rejected communication control information storage medium

in connection with the communication relating to the message arrival from the communication

partner not registered in said receipt-allowed communication partner registering table includes

date-and-time information at the time of the message arrival.

17. (currently amended) A facsimile device provided with a receipt-rejected function of

rejecting message receipt from a communication partner other than communication partners

previously registered in a receipt-allowed communication partner registering table, said facsimile

device comprising:

a receipt-rejected communication control medium collecting [[the]] communication

control information in connection with [[the]] a communication relating to the message arrival

from the communication partner not registered in said receipt-allowed communication partner

registering table, and storing said collected communication control information in a receipt-

rejected communication control information storage medium;

a communication control list creating medium creating a list of image information on the

basis of the communication control information stored in said receipt-rejected communication control information storage medium; and

a list outputting medium visibly outputting said list of image information created by said communication control list creating medium,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registering table is rejected, a facsimile receiving process is not performed by said facsimile device for the receipt-rejected communication, and

wherein <u>for a receipt-rejected communication partner,</u> said list of image information ~~includes communication control information for~~ <u>shows</u> a plurality of rejected communications, ~~and the communication control information in the list for a rejected communication indicates that the communication was rejected~~ <u>from the receipt-rejected communication partner including for each rejected communication from the receipt-rejected communication partner the date and time of the rejected communication.</u>

18. (currently amended) A method of controlling a facsimile device provided with a receipt-rejected function of rejecting message receipt from a communication partner other than a communication partner previously registered in a receipt-allowed communication partner registering table, said method comprising the steps of:

collecting communication control information in connection with [[the]] <u>a</u> communication relating to <u>the</u> message arrival from [[a]] <u>the</u> communication partner not registered in said receipt-allowed communication partner registering table;

storing said collected communication control information in a receipt-rejected

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 13

communication control information storage medium;

creating a list of image information on the basis of the communication control

information stored in said receipt-rejected communication control information storage medium;

and

visibly outputting said created list of image information,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registering

table is rejected, a facsimile receiving process is not performed by said facsimile device for the

receipt-rejected communication, and

wherein for a receipt-rejected communication partner, said list of image information

~~includes communication control information for~~ shows a plurality of rejected communications;

~~and the communication control information in the list for a rejected communication indicates that~~

~~the communication was rejected~~ from the receipt-rejected communication partner including for

each rejected communication from the receipt-rejected communication partner the date and time

of the rejected communication.

19. (currently amended) A facsimile device provided with a receipt-rejected function of

rejecting message receipt from a communication partner other than communication partners

previously registered in a receipt-allowed communication partner registering table, said facsimile

device comprising:

a normal communication control medium collecting communication control information

in connection with [[the]] a communication relating to a message receipt from a registered

communication partner registered in a transmission-allowed communication partner registering

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 14

table or in said receipt-allowed communication partner registering table and storing said collected

communication control information in said normal communication control information storage

medium;

a receipt-rejected communication control medium collecting [[the]] communication

control information in connection with [[the]] a communication relating to [[the]] message

arrival from the communication partner not registered in said receipt-allowed communication

partner registering table, and storing said collected communication control information in a

receipt-rejected communication control information storage medium;

a communication control list creating medium creating a list of image information on the

basis of the communication control information respectively stored in said normal

communication control information storage medium and said receipt-rejected communication

control information storage medium and creating communication control information in

connection with the communication relating, to the message arrival from the communication

partner not registered in said receipt-allowed communication partner registering table, such that

both of said communication control information can be discriminated from the communication

control information in connection with the communication relating to the message receipt from

the communication partner registered in the transmission communication partner registering table

or in said receipt-allowed communication partner registering table; and

a list outputting medium visibly outputting said list of image information created by said

communication control list creating medium,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registering

table is rejected, a facsimile receiving process is not performed by said facsimile device for the

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 15

receipt-rejected communication, and

wherein ~~for a receipt-rejected communication partner,~~ said list of image information ~~includes communication control information for~~ shows a plurality of rejected communications, ~~and the communication control information in the list for a rejected communication indicates that the communication was rejected~~ from the receipt-rejected communication partner including for each rejected communication from the receipt-rejected communication partner the date and time of the rejected communication.

20. (currently amended) A method of controlling a facsimile device provided with a receipt-rejected function of rejecting message receipt from a communication partner other than communication partners previously registered in a receipt-allowed communication partner registering table, said method comprising the steps of:

collecting communication control information in connection with communication relating to [[the]] message receipt from [[the]] a communication partner registered in [[the]] a transmission-allowed communication partner registering table or in said receipt-allowed communication partner registering table;

storing said collected communication control information in said normal communication control information storage medium;

collecting [[the]] communication control information in connection with communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table;

storing said collected communication control information in said receipt-rejected communication control information storing medium;

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 16

creating the list of image information on the basis of the communication control information respectively stored in said normal communication control information storing medium and said receipt-rejected communication control information storing medium and creating the communication control information in connection with communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, such that both of said communication control information can be discriminated from the communication control information in connection with the communication relating to the. message receipt from the communication partner registered in the transmission communication partner registering table or in said receipt-allowed communication partner registering table; and

visibly outputting said list of image information created by said communication control list creating medium,

wherein when said communication relating to the message arrival from said communication partner not registered in said receipt-allowed communication partner registering table is rejected, a facsimile receiving process is not performed by said facsimile device for the receipt-rejected communication, and

wherein for a receipt-rejected communication partner, said list of image information ~~includes communication control information for~~ shows a plurality of rejected communications; ~~and the communication control information in the list for a rejected communication indicates that the communication was rejected~~ from the receipt-rejected communication partner including for each rejected communication from the receipt-rejected communication partner the date and time of the rejected communication.

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 17

21. (original) The facsimile device provided with a receipt-rejecting function as defined in claim 17, wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

22. (original) The facsimile device provided with a receipt-rejecting function as defined in claim 19, wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

23. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 18, wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

24. (original) The method of controlling the facsimile device provided with a receipt-

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 18

rejecting function as defined in claim 20, wherein the communication control information collected by said receipt-rejected communication control medium and stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

25. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 18, wherein the communication control information memorized in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

26. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 20, wherein the communication control information stored in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table includes a communication partner identifying information.

27. (original) The facsimile device provided with a receipt-rejecting functions as defined in claim 17,

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 19

wherein said facsimile device further comprises a time counting medium for counting the

present date and time; and

wherein the communication control information collected by said receipt-rejected

communication control medium and storing in said receipt-rejected communication control

information memorizing medium in connection with the communication relating to the message

arrival from the communication partner not registered in said receipt-allowed communication

partner registering table includes the date-and-time information read out from said time counting

medium at the time of the message arrival.

28. (original) The facsimile device provided with a receipt-rejecting functions as defined

in claim 19,

wherein said facsimile device further comprises a time counting medium for counting the

present date and time; and

wherein the communication control information collected by said receipt-rejected

communication control medium and storing in said receipt-rejected communication control

information storing medium in connection with the communication relating to the message

arrival from the communication partner not registered in said receipt-allowed communication

partner registering table includes the date-and-time information read out from said time counting

medium at the time of the message arrival.

29. (original) The facsimile device provided with a receipt-rejecting, functions as

defined in claim 21,

wherein said facsimile device further comprises a time counting medium for counting the

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 20

present date and time; and

wherein the communication control information collected by said receipt-rejected

communication control medium and stored in said receipt-rejected communication control

information storing medium in connection with the communication relating to the message

arrival from the communication partner not registered in said receipt-allowed communication

partner registering table includes the date-and-time information read out from said time counting

medium at the time of the message arrival.

30. (original) The facsimile device provided with a receipt-rejecting functions as defined

in claim 22,

wherein said facsimile device further comprises a time counting medium for counting the

present date and time; and

wherein the communication control information collected by said receipt-rejected

communication control medium and stored in said receipt-rejected communication control

information storing medium in connection with the communication relating to the message

arrival from the communication partner not registered in said receipt-allowed communication

partner registering table includes the date-and-time information read out from said time counting

medium at the time of the message arrival.

31. (original) The method of controlling the facsimile device provided with a receipt-

rejecting function as defined in claim 18 further comprising the steps of:

counting the present date and time by use of a time counting medium;

collecting said communication control information by use of said receipt-rejected

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 21

communication control medium; and

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out from said time counting medium at the time of the message arrival.

32. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 20 further comprising the steps of:

counting the present date and time by use of a time counting medium;

collecting said communication control information by use of said receipt-rejected communication control medium; and

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out from said time counting medium at the time of the message arrival.

33. (original) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 23 further comprising the steps of:

counting the present date and time by use of a time counting medium;

collecting said communication control information by use of said receipt-rejected communication control medium; and

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 22

storing said collected communication control information in said receipt-rejected

communication control information storing medium in connection with the communication

relating to the message arrival from the communication partner not registered in said receipt-

allowed communication partner registering table so as to include the date-and-time information

read out from said time counting medium at the time of the message arrival.

34. (original) The method of controlling the facsimile device provided with a receipt-

rejecting function as defined in claim 24 further comprising the steps of:

counting the present date and time by use of a time counting medium;

collecting said communication control information by use of said receipt-rejected

communication control medium; and

storing said collected communication control information in said receipt-rejected

communication control information storing medium in connection with the communication

relating to the message arrival from the communication partner not registered in said receipt-

allowed communication partner registering table so as to include the date-and-time information

read out from said time counting medium at the time of the message arrival.

35. (previously presented) The method of controlling the facsimile device provided with

a receipt-rejecting function as defined in claim 18 further comprising the step of:

storing said collected communication control information in said receipt-rejected

communication control information storing medium in connection with the communication

relating to the message arrival from the communication partner not registered in said receipt-

allowed communication partner registering table so as to include the date-and-time information

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 23

read out at the time of the message arrival.

36. (previously presented) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 20 further comprising the step of:

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table, so as to include the date-and-time information read out at the time of the message arrival.

37. (previously presented) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 23 further comprising the step of:

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-allowed communication partner registering table so as to include the date-and-time information read out at the time of the message arrival.

38. (previously presented) The method of controlling the facsimile device provided with a receipt-rejecting function as defined in claim 24 further comprising the step of:

storing said collected communication control information in said receipt-rejected communication control information storing medium in connection with the communication relating to the message arrival from the communication partner not registered in said receipt-

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 24

allowed communication partner registering table so as to include the date-and-time information

read out at the time of the message arrival.

39. (currently amended) A communication terminal device provided with a function of

rejecting the receipt of messages from communication partners excluding a communication

partner previously registered in a receipt-allowed communication partner registration table, said

communication terminal device comprising:

receipt rejecting communication control means collecting communication control

information in connection with [[the]] a communication relating to [[the]] message arrival from a

communication partner not registered in said receipt-allowed communication partner registration

table, and storing said collected communication control information in signal-receiving rejecting

communication control information storing means;

communication control list creating means creating a list of image information on the

basis of said communication control information stored in said signal-receiving rejecting

communication control information storing means; and

list outputting means visibly outputting said list of image information created by said

communication control list creating means,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registration

table is rejected, a message receiving process is not performed by said communication terminal

device for the receipt-rejected communication, and

wherein for a receipt-rejected communication partner, said list of image information

includes communication control information for shows a plurality of rejected communications;

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 25

and the communication control information in the list for a rejected communication indicates that
the communication was rejected from the receipt-rejected communication partner including for
each rejected communication from the receipt-rejected communication partner the date and time
of the rejected communication.

40. (currently amended) A communication terminal device provided with a function of
rejecting the receipt of messages from communication partners excluding a communication
partner previously registered in a receipt-allowed communication partner registration table, said
communication terminal device comprising:

normal communication control means collecting communication control information in
connection with [[the]] a communication relating to [[the]] receipt of [[the]] message from [[the]]
a communication partner registered in a transmission-allowed communication partner registration
table or said receipt-allowed communication partner registration table, and storing said collected
communication control information in said normal communication control information storing
means;

receipt-rejected communication control means collecting said communication control
information in connection with the communication relating to the message arrival from a
communication partner not registered in said receipt-allowed communication partner registration
table and storing said corrected communication control information in a receipt-rejected
communication control information memorizing means;

communication control list creating means creating said communication control list such
that a list of image information based on the communication control information respectively
stored in said normal communication control information storing means and said receipt-rejected

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 26

communication control information storing means, and the communication control information in

connection with the communication relating to the message arrival from the communication

partner not registered in said receipt-allowed communication partner registering table can be

discriminated from the communication control information in connection with the

communication relating to the receipt of the messages from the communication partner registered

in a transmission-allowed communication registering table; and

list outputting means visibly outputting the list of image information created by said

communication control list creating means,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registration

table is rejected, a message receiving process is not performed by said communication terminal

device for the receipt-rejected communication, and

wherein <u>for a receipt-rejected communication partner,</u> said list of image information

~~includes communication control information for~~ <u>shows</u> a plurality of rejected communications,

~~and the communication control information in the list for a rejected communication indicates that~~

~~the communication was rejected~~ <u>from the receipt-rejected communication partner including for</u>

<u>each rejected communication from the receipt-rejected communication partner the date and time</u>

<u>of the rejected communication.</u>

41. (currently amended) A facsimile device provided with a receipt-rejected function of

rejecting the message receipt from a communication partner excluding communication partners

previously registered in a receipt-allowed communication partner registered in a receipt-allowed

communication partner registering table, said facsimile device comprising:

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 27

receipt-rejected communication control means collecting [[the]] communication control

information in connection with [[the]] a communication relating to [[the]] message arrival from

the communication partner not registered in said receipt-allowed communication partner

registering table, and storing said collected communication control information in said receipt-

rejected communication control information storing means;

communication control list creating means creating a list of image information on the

basis of the communication control information stored in said receipt-rejected communication

control information storing means; and

list outputting means visibly outputting said list of image information created by said

communication control list creating means,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registering

table is rejected, a message receiving process is not performed by said facsimile device for the

receipt-rejected communication, and

wherein for a receipt-rejected communication partner, said list of image information

includes communication control information for shows a plurality of rejected communications,

and the communication control information in the list for a rejected communication indicates that

the communication was rejected from the receipt-rejected communication partner including for

each rejected communication from the receipt-rejected communication partner the date and time

of the rejected communication.

42. (currently amended) A facsimile device provided with a receipt-rejected function of

rejecting the message receipt from a communication partner excluding communication partners

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 28

previously registered in a receipt-allowed communication partner registering table, said facsimile

device comprising:

normal communication control means collecting [[the]] communication control

information in connection with [[the]] a communication relating to [[the]] message receipt from

[[the]] a communication partner registered in [[the]] a transmission-allowed communication

partner registering table or in said receipt-allowed communication partner registering table and

storing said collected communication control information in said normal communication control

information storing means;

receipt-rejected communication control means collecting [[the]] communication control

information in connection with [[the]] a communication relating to [[the]] message arrival from

the communication partner not registered in said receipt-allowed communication partner

registering table, and storing said collected communication control information in said receipt-

rejected communication control information storing means;

communication control list creating means creating the list of image information on the

basis of the communication control information respectively memorized in said normal

communication control information storing means and said receipt-rejected communication

control information storing means and creating the communication control information in

connection with the communication relating to the message arrival from the communication

partner not registered in said receipt-allowed communication partner registering table, such that

both of said communication control information can be discriminated from the communication

control information in connection with the communication relating to the message receipt from

the communication partner registered in the transmission communication partner registering table

or in said receipt-allowed communication partner registering table; and

Koichiro MAEMURA, S.N. 09/653,994   Dkt. 2271/62975
Page 29

list outputting means visibly outputting said list of image information created by said

communication control list creating means,

wherein when said communication relating to the message arrival from said

communication partner not registered in said receipt-allowed communication partner registering

table is rejected, a message receiving process is not performed by said facsimile device for the

receipt-rejected communication, and

wherein for a receipt-rejected communication partner, said list of image information

includes communication control information for shows a plurality of rejected communications,

and the communication control information in the list for a rejected communication indicates that

the communication was rejected from the receipt-rejected communication partner including for

each rejected communication from the receipt-rejected communication partner the date and time

of the rejected communication.

Claims 43-44 (canceled).